

LTAB3020T

TVI Transmitter



Key features

- Compatible with HDTV/AHD/CVI signal
- Transmission signal: 720P/1080P
- Cable: CAT 5/5e/6
- Transmission distance:
- 720P TVI: up to 250M; 1080P TVI: up to 250M
- 720P AHD: up to 350M
- 720P CVI: up to 400M; 1080P CVI: up to 200M

LTAB3020T		
Properties	Transmission signal	1 channel
	Transmission distance	720P TVI: 250m (max) / 1080P TVI: 250m (max); 720P AHD:350m(max); 720P CVI: 400m(max)/1080P CVI: 200m(max)
	Category Type	UTP CAT5/5E/6
Video transmission properties and port	Coaxial video connector	BNC-M
	Twisted-pair video	Push-terminal
	Compatible Format	HDTV/AHD/CVI
	Resolution	720P/1080P
	Anti-interference	>60db
Protection	ESD	1a contact discharge electricity level 3
		1b air discharge electricity level 3
		Per: IEC61000-4-2
	Coaxial cable connector	2KV(common-code) Per: IEC1000-4-5
	UTP Cable Connector	2KV(different-code), 4KV(common-code), Per: IEC1000-4-5
Impedance	BNC male	75 ohms
	UTP cable	100 ohms
Physical Properties	Dimension (L*W*H)	2" x 0.8" x0.7"(53mm x 20mm x 17mm)
	Shell	ABS
	Color	Black
	N. W.	25g
Stability	MTBF	>10000H
Environmental	Operating Temperature	-10-55℃
	Storage Temperature	-20-70℃
	Humidity	0-95% (non-condensing)