

Platinum 4-in-1 Analog Covert Camera CM1925T-IR




Key Features:

- Full HD 1080P
- 1/2.9" Sensor
- 3.7mm Lens
- Support UTC Function
- Support 2D/3D NR, DWDR
- DC 12V
- IR up to 49ft(15m)
- TVI / CVI / AHD / CVBS 4 in 1 Solution





Dimensions:

















Platinum 4-in-1 Analog Covert Camera CM1925T-IR

a	
CAMERA	
Image Sensor	1/2.9" CMOS
Signal System	NTSC/PAL
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.1 Lux,0 Lux (with IR on)
Shutter Speed	1/30(1/ 25)s to 1/50,000 s
Lens	3.7mm Lens
Synchronization	Internal
Video Frame Rate	1080p@30fps/1080p@25fps
Digital Noise Reduction	2D NR & 3D NR
S/N Ratio	More than 50dB
Video Output	TVI / CVI / AHD / CVBS 4-in-1 Switchable
IR	
IR Wavelength	940nm
IR Distance	33~49ft(10~15m)
GENERAL	
Working Temperature	14 ° F - 122 ° F (-10 ° C - 50 ° C)
/Humidity	Humidity 85% or less (non-condensing)
Power Supply	DC 12V
Power Consumption	Max. 12 W (When the IR on)
Dimension	2.7" x 4.7" x 1.9" (69mm x 120mm x 47mm)
Weight	0.4lb(200g)