

## Platinum Dome HD-TVI Motoried Camera 3.1MP CMHD35T3DW-Z



## **Key Features:**

- 3.1MP High Definition
- 2.8-12mm Motorized Varifocal Lens
- True WDR 120dB
- 2 Matrix IR LED up to 131ft.(40m)
- DC 12V, AC 24V
- OSD menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof
- 3-axis
- Must be used with HD-TVI 3.0 DVRs










**Dimensions:** 



Unit mm























## Platinum Dome HD-TVI Motorized Camera 3.1MP CMHD35T3DW-Z

CAMERA	
Image Sensor	1/3"CMOS
Signal System	NTSC/PAL
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Lens	2.8-12mm Motorized Varifocal Lens
Shutter Speed	1/30(1/25) s to 1/50,000 s
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1920x1536@18fps
HD Video Output	1 HD-TVI Output
S/N Ratio	More than 62dB
MENU	
AGC	Support
D/N Mode	Color/ BW/ SMART
White Balance	ATW/ MWB
BLC	Support
Function	True WDR, DNR, Mirror, SMART IR
GENERAL	
Working Temperature	-40 ° F - 140 ° F (-40 ° C - 60 ° C)
/Humidity	Humidity 90% or less (non-condensing)
Power Supply	DC 12V, AC 24V
Power Consumption	Max. 6.5W
Weather Proof Ratings	IP66
IR Range	Up to 131ft(40m)
Impact Protection	IK10
Dimension	5.8 "×4.9" (145.2×124.1mm)
Weight	3.5lb(1600g)