

CMHR6232


HD720P HD-TVI Bullet Camera



Key features

- HD720P Video Output
- Adopt HDTV Technology
- True Day/Night
- DNR, Smart IR
- 65ft(20m) IR distance
- IP66 weatherproof

Dimensions



CMHR6232	
Camera	
Image Sensor	1/3" Sensor
Signal System	NTSC/PAL(Euro Version)
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	NTSC: 1/30 s(PAL: 1/25 s) to 1/50,000 s
Lens	3.6mm
	Angle of View: 76.88°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	NTSC: 720p@30fps/PAL: 720p@25fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 52dB
General	
Working Temperature /Humidity	-40 ° F - 140 ° F (-40 ° C - 60 ° C) Humidity 90% or less (non-condensing)
Power Supply	12V DC
Power Consumption	Max. 3.5W
Weather Proof Ratings	IP66
IR Range	Up to 65ft(20m)
Dimensions	φ 2.8" × 5.9" (φ 70.0×149.5 mm)
Weight	0.8lb(360g)