

Platinum HD-TVI Bullet Camera 2.1MP CMHR6422W-28







Key Features:

- 2.1MP High Definition
- 1920x1080P@30fps
- 2.8mm Fixed Lens
- True 120dB WDR
- 2 Matrix IR up to 65ft(20m)
- DC 12V
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

Dimensions:







Unit mm

















©2016 LT Security, Inc. | info@LTSecurityinc.com | www.LTSecurityinc.com













Platinum HD-TVI Bullet Camera 2.1MP CMHR6422W-28

| CAMERA | |
|-----------------------|---|
| Image Sensor | 1/2.7"CMOS |
| Signal System | NTSC/PAL |
| Effective Pixels | 1928(H)*1088(V) |
| Min. Illumination | 0.01 Lux, 0 Lux with IR |
| Shutter Speed | 1/30(1/25) s to 1/50,000 s |
| Lens | 2.8mm |
| Day & Night | ICR |
| Synchronization | Internal |
| Video Frame Rate | 1080p@30fps/1080p@25fps |
| HD Video Output | 1 HD-TVI Output |
| S/N Ratio | More than 62dB |
| MENU | |
| | |
| AGC | Support |
| D/N Mode | Color/ BW/ SMART |
| White Balance | ATW/ MWB |
| BLC | Support |
| Function | True WDR, DNR, Mirror, SMART IR |
| GENERAL | |
| Working Temperature | -40 ° F - 140 ° F (-40 ° C - 60 ° C) |
| /Humidity | Humidity 90% or less (non-condensing) |
| Power Supply | DC 12V |
| Power Consumption | Max. 5W |
| Weather Proof Ratings | IP66 |
| IR Range | Up to 65ft(20m) |
| | 2.3 "×2.2" ×6.1"(58.5×55.5 × 153.6mm) |
| Dimension | 2.5 \ \ \ 2.2 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ |