


LTN9664-R


Embedded NVR



Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- 8 SATA interfaces, up to 6TB for each disk
- Support NAS, IP SAN Network Storage, 4 x POS
- HDD quota and group management
- Dual gigabit network interfaces
- RAID 0,1,5,10 supported

Rear Panel of LTN9664-R



1. Video out
2. CVBS audio out and VGA audio out
3. Line in
4. RS-232 serial interface
5. VGA interface
6. HDMI interface
7. eSATA interface
8. LAN1, LAN2 network interface
9. Termination switch
10. RS-485 serial interface, keyboard interface, alarm in and alarm out
11. GND
12. 100 ~ 240VAC Power Input
13. Power Switch
14. USB Interface

LTN9664-R	
Video/Audio input	
IP video input	64-ch
Two-way audio input	1-ch, BNC (2.0 Vp-p, 1 kΩ)
Incoming bandwidth	160Mbps
Video/Audio output	
Recording resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω) Resolution: 704 × 576 (PAL); 704 × 480 (NTSC)
HDMI output	1-ch, resolution: 1920 × 1080P/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
VGA output	1-ch, resolution: 1920 × 1080P/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768 /60Hz
Audio output	2-ch, BNC (Linear, 600 Ω)
Playback resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous playback	16-ch
Hard disk	
SATA	Up to 8 SATA interfaces
eSATA	1 eSATA interface
Capacity	Up to 6TB capacity for each disk
Disk array	
Array type	RAID0, RAID1, RAID5, RAID10
Number of array	4
Number of virtual disk	8
External interface	
Network interface	2, 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interfaces	RS-232, RS-485, RS-485 keyboard
USB interface	3 x USB2.0
Alarm in	16
Alarm out	4
General	
Power supply	100 ~ 240 VAC, 6.3A, 50 ~ 60Hz
Consumption	≤ 40W
Working temperature	-10° C ~ +55° C (14° F ~ 131° F)
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 2U chassis
Dimensions (WxDxH)	445 × 470 × 90 mm (17.52" × 18.5" × 3.54")
Weight	≤ 8 kg (17.64 lb) (without hard disk or DVD-R/W)