

LTAB1011R—Active Video Balun Transmitter & Receiver

FEATURE

- Single Channel Active Video Receiver
- Long Distance Transmission of PAL /NTSC Real-time Video
- DSA
- Transmission of Single Channel Data
- Exceptional Interference Rejection
- Options for Distances : Three Levels
- Red Light for Power ,Green Light for Video
- Built -in Surge Protection ,Lighting Protection and other Protection Settings
- Convenient Wiring , Higher Cable Utilization Rate and Lower Composite Wiring Cost;Wiring Cost, Compact Size and Cabinet Installation



SPECIFICATIONS

Specifications		LTAB1011R
Video	Frequency	DC to 8MHz
	Impedance	Coax BNC 75Ω; UTP 100Ω
	CMRR	60dB
	Attenuation	0.3dB
Environment	Working Temp.	-10°C ~ 50°C
	Storage Temp.	-30°C ~ 70°C
	Humidity	0% ~ 95%
UTP Wire	Category Type	UTP Cat5, 24 - 16 AWG
	Impedance	9Ω (100m)
Power		DC12V
UTP Port		Terminal Block
Packing	Quantity in Box	1PC
	Box Weight	40g
	Box Dimension	78 x38 x36mm
	Box Quantity Per Carton	200pcs
	Carton Net Weight	8kg
	Carton Gross Weight	8.5kg
Carton Dimension	590*275*435(mm)	

