

Platinum Enterprise Level 8 Channel NVR 1U


LTN8608-P8



Key Features:

Rear Panel:

- Up to 8 network cameras can be connected
 - Support live view, storage, and playback of the connected camera with up to the resolution of 12 megapixels
 - Up to 8 independent PoE network interfaces for different models
 - HDMI Video output at up to 4K (3840 × 2160) resolution
 - Up to 2 SATA hard disks can be connected with up to 6TB capacity for each
 - Supports HDD quota and group modes
- 1. Audio in
 - 2. Audio out
 - 3. VGA Interface
 - 4. HDMI Interface
 - 5. Alarm in/out
 - 6. LAN Network Interfaces
 - 7. USB 3.0 Interface
 - 8. GND
 - 9. 100~240VAC Power Input
 - 10. Power Switch
 - 11. Network Interfaces with PoE function
 - 12. Video out



Platinum Enterprise Level 8 Channel NVR 1U

LTN8608-P8

Video/Audio Input	
IP video Input	8-CH, Up to 12 MP resolution
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Network	
Incoming bandwidth	80 Mbps
Outgoing bandwidth	256Mbps
Remote connection	128
Video/Audio Output	
Recording resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
HDMI output	4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA output	1-ch, resolution: 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
CVBS output	1-ch
Audio output	1-ch, RCA (Linear, 1kΩ)
Decoding	
Decoding format	H.265/H.264 Zip+/H.264/MPEG4
Live view / Playback resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	8-CH
Capability	2-ch @ 4K, or 8-ch @ 1080p
Hard Disk	
SATA	2 SATA interfaces for 2 HDDs
Capacity	Up to 6TB for each disk
External Interface	
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
Alarm in/out	4/1
PoE	
Interface	8 RJ-45 10/100 Mbps self-adaptive Ethernet interfaces
Max. Power	≤ 120W
Supported standard	IEEE 802.3 af/at
GENERAL	
Power Supply	100~240V AC
Consumption	≤ 15 W (without enabling PoE)
Working Temperature	+14 ° F ~ +131 ° F (-10 ° C ~ +55 ° C)
Working Humidity	10% - 90%
Casing	380mm rack-mounted 1U casing
Dimensions (WxDxH)	15.0" × 12.4" × 2.0" (380 × 315 × 52mm)
Weight	≤ 7.3lb (3.3 Kg)