

## *8 MP Pro-X Intelligent Fixed Lens Series*

# LXIP3582W-28MDA



### Key Features

- Resolutions up to 8 MP (3840 × 2160) @ 30 fps, 8 MP (3840 × 2160) @ 20 fps with AI enabled
- 1/2.8" Starlight CMOS image sensor
- Min. illumination 0.005 Lux @ f1.4 (Color, 30 IRE), 0 Lux with IR light on
- Built-in IR LED, Matrix IR LED up to 98 feet
- Smart encoding H.264 / H.265
- 120 dB True WDR, 3D DNR, HLC, BLC
- Motion Detection 2.0 focuses on persons & vehicles
- Smart VCA by AI algorithm
- Built-in MicroSD card storage up to 256 GB
- Built-in Mic
- 12 VDC / POE power supply
- IP67 protection rating

## LXIP3582W-28MDA


### Specifications

Camera	
Image Sensor	1/2.8" 8 MP progressive CMOS
Min. Illumination	0.005 Lux @ f1.4 (Color, 30 IRE), 0.0005 Lux @ f1.4 (B&W, 30 IRE), 0 Lux (illuminator on)
Shutter Speed	Auto / Manual 1/3 - 1/100,000 sec.
S/N Ratio	> 56 dB
Noise Reduction	3D DNR
Wide Dynamic Range	120 dB
Day & Night Imaging	Auto (ICR) / Color / B&W
Angle Adjustment	Pan: 0° - 360°, Tilt: 0° - 78°, Rotation: 0° - 360°
Lens Type	Fixed, 2.8 mm @ f1.4
Iris Type	Fixed
Field of View	Horizontal 108° × Vertical 58° × Diagonal 127°
Close Focus Range	4.6 ft (1.4 m)
DORI	Detect: 280.5 ft (85.5 m), Observe: 112.2 ft (34.2 m), Recognize: 56.1 ft (17.1 m), Identify: 28.2 ft (8.6 m)
Illuminator	2 (IR LED)
Illumination Range	98.4 ft (30 m)
Illuminator Control	Auto / Manual
Video	
Video Compression	MJPEG (only supported by sub stream), H.264, H.264H, H.264B, H.265
Smart Codec	Supported
Resolution	8 MP (3840 × 2160), 6 MP (3072 × 2048), 5 MP (3072 × 1728 / 2592 × 1944), 4 MP (2688 × 1520), 3 MP (2048 × 1536 / 2304 × 1296), 1080p (1920 × 1080), 1.3 MP (1280 × 960), 720p (1280 × 720), D1 (704 × 576 / 704 × 480), VGA (640 × 480), CIF (352 × 288 / 352 × 240)
Video Frame Rates	Main stream: 3840 × 2160 @ 1-20 fps by default <b>or</b> 3840 × 2160 @ 1 - 30 fps when AI function disabled Sub stream: 704 × 576 @ 1 - 25 fps or 704 × 480 @ 1 - 30 fps Third stream: 1920 × 1080 @ 1 - 30 fps
Video Stream	3 streams
Bit Rate Control	CBR, VBR
Video Bit Rates	H.264: 3 Kbps - 8,192 Kbps H.265: 3 Kbps - 8,192 Kbps
ROI	Supported (4 areas)
Image Rotation	0° / 90° / 180° / 270° (supports 90° / 270° with 1920 × 1080 resolution or lower)
Mirror	Supported
Privacy Mask	Supported (4 areas)
Audio	
Built-in Mic	Yes
Audio Compression	G.711 a, G.711 Mu, G726
Intelligent Analysis	
VCA	Tripwire, intrusion (supports classification and accurate detection of vehicles and persons)
MD 2.0	Yes, supports alarm triggered by vehicles and persons)
Event Types	

Alarm events	No SD card, SD card full, SD card error, service life warning (only supported by card), network disconnection, IP conflict, illegal access, motion detection, video tampering, intrusion, tripwire, scene changing, audio detection, voltage detection, IMD, safety exceptions / anomalies
<b>Network</b>	
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP
Interoperability	ONVIF (Profile S / Profile G / Profile T), API, P2P
Storage	FTP, SFTP, Micro SD Card (supports up to 256 GB), Cloud, NAS
Web Browsers	IE: IE8, IE9, IE11, Chrome, Firefox
Client	Pro-X, X Station
<b>Interface</b>	
Network	RJ-45 (10/100 Base-T)
<b>General</b>	
Power	12 VDC / PoE (802.3af), <7.9 W
Housing	Aluminum alloy body, except for trim ring
Dimensions	4.15 × Φ 4.8" (105.4 × Φ 122.0 mm)
Operating Conditions	-40° to 140° F (-40° to 60° C), less than 95% RH
Storage Conditions	-40° to 140° F (-40° to 60° C)
Protections	IP67
Net Weight	1.2 lb (0.55 kg)
Gross Weight	1.5 lb (0.69 kg)
Certifications	FCC

### Dimensions (mm[inch])

mm [inch]



Accessories

LXJB02 Junction Box	LXWM01 Wall Mount	LXPM01 Vertical Pole Mount	LXPM02 Horizontal Pole Mount	LXKPD01 Pendant Mount	LXCM01 Corner Mount
					

