

## LTAH014LN

### 1X4 HDMI Splitter, 4KX2K 30HZ, Version 1.4b, 3D



#### Introduction:

This 1x4 HDMI splitter uses a single HDMI source, accessing to multiple HDMI sinks .It allows one HDMI device to be split easily to four HDMI compatible monitors or projectors. In addition, it can also be placed at the end of a long HDMI cable to regenerate the HDMI signal. The resolution of this HDMI splitter can be up to 3840X2160/30HZ.

#### Features :

- ✧ Support HDMI 1.4b version
- ✧ Support 3D video format
- ✧ Support high resolution up to 3840X2160/30HZ
- ✧ Support highest rate of 3.4 G and TMDS clock can be up to 340 MHz
- ✧ Support 8/10/12 bit deep color
- ✧ Support AWG26 HDMI standard cable: input up to 33ft(10 m), output up to 49ft(15 m). (when the resolution is 4K, input up to 26ft(8 m), output up to 26ft(8 m).)
- ✧ Support one single HDMI source, accessing to multiple HDMI sinks, the source can be DVD player, A/V receiver, set top box, etc. 5V/1A power adapter

## Specifications:

HDMI version :	HDMI 1.4b
HDMI resolution:	up to 3840*2160/30Hz
Support video format:	8/10/12 bit deep color
Support audio format:	DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD
Max bandwidth:	340MHz
Max baud rate:	3.4Gbps
Input cable distance:	1080p resolution ≤33ft, 4K resolution ≤26ft AWG26 HDMI standard cable
Output cable distance:	1080p resolution ≤49ft, 4K resolution ≤26ft AWG26 HDMI standard cable
Max working current:	500mA
Power adapter format:	input AC (50HZ, 60HZ) 100V-240V; output: DC5V/1A
Operating Temperature range:	5°F ~131°F (-15~55°C)
Dimension (L x W x H) :	7.0"x2.6"x0.79"(178x66x20 mm)
Weight:	0.24lb.(110g)