

## *IP Speaker*

# LXA2WSP-120D



### Key Features

- Supports wall and pole mount installations
- POE+ (802.3at)
- Built-in reset button
- 512 MB TF card for storage expansion
- Supports uploading custom audio
- Supports remote management over web pages

# Specifications

LXA2WSP-120D

## Microphone

Type	Built-in microphone
Pickup Distance	9.8 ft (≥ 3 m)
Frequency Response	50 Hz - 12 KHz

## Speaker

Max Sound Pressure Level	108 dB
SNR	≥75 dB
Frequency Response	250 Hz - 16 KHz
Coverage Pattern	H: 70°; V: 100°

## Network

Network Port	1 × RJ-45 port
Network Protocol	TCP, UDP, HTTP, SIP, ONVIF

## General

Audio Protocol	MP3, G.711a/u
Storage	TF card, 512 MB max
Power Input	PoE+ (IEEE 802.3at), 24 VDC/1 A
Power Consumption	15W
Operating Temperature	-40° to 140° F (-40° to 60° C)
Operating Humidity	60% - 95% RH, non-condensing
Protection	IP66
Certifications	FCC: 47 CFR FCC Part 15
Product Dimensions (L × W × H)	8.86 × 6.69 × 9.84" (225 × 170 × 250 mm)
Net Weight	3.97 lb (1.8 kg)
Gross Weight	5.51 lb (2.5 kg)

Dimensions (mm [inch])

